AUDI 100/A6/S4/S6 1992-98

SECTION INDEX A/C /HEATER/VENTILATION. 117 A/C REFRIGERANT CAPACITIES. 117 ABS/BRAKES.. 120 AIR BAG SYSTEM .. 120 AIR CLEANER ... 124 BACK WINDOW 131 CENTER CONSOLE. 126 CLEAR COAT IDENTIFICATION... 115 COOLING COWL & DASH 125 ELECTRICAL 124 EMISSION SYSTEM. 124 ENGINE COVER. 123 ENGINE OIL COOLER. 117 ENGINE/TRANS. 123 ENGINE/TRANS MOUNTS. 123 EXHALIST. 124 FRONT BUMPER. 115 FRONT DOOR .. 128 FRONT DRIVE AXLE. 122 FRONT FENDER .. 118 FRONT INNER STRUCTURE... 119 FRONT LAMPS. 115 FRONT STEERING LINKAGE/GEAR. 122 FRONT SUSPENSION121 FUEL TANK 135 GRILLE.... 115 HOOD ... 116 INFORMATION LABELS ... 115 INSTRUMENT PANEL. 125 INTERCOOLER 117 LIFTGATE .. 133 LÚGGAGE LID.. 133 PAINT CODE LOCATION. 114 QUARTER GLASS ... 133 QUARTER PANEL. 131 REAR BODY 135 REAR BUMPER. 136 REAR DOOR... 129 REAR DRIVE AXLE. 135 REAR LAMPS ... 135 REAR SUSPENSION... 134 ROCKER/PILLARS/FLOOR. 127 ROOF .. 130 SEAT. 127 SEAT BELTS .. 127 SPECIAL CAUTIONS. 114 STEERING PUMP... 122 STEERING WHEEL/COLUMN. 122 SUNROOF. 131 TURBOCHARGER... 124 UNDERHOOD DIMENSIONS 119 WHEEL 120 WINDSHIELD 125

SPECIAL CAUTIONS

SUPPLEMENTAL RESTRAINT SYSTEM

Refer to Procedure Explanation 29 for Supplemental Restraint/Air Bag Special Cautions.

ABS

Manufacturer advises that ABS Control Unit be disconnected before welding and removed if a temperature of 85 degrees C (185 degrees F) is to be exceeded for more than 2 hours.

REFINISH BAKING

Manufacturer advises that after baking, sufficient cooling time should be allowed before attempting to start vehicle.

SUSPENSION

Manufacturer advises that some new fasteners must be used whenever old fasteners are loosened or removed.

PAINT CODE LOCATION

Paint code located on luggage compartment floor.